

TP-3250H

THERMAL RECEIPT PRINTER



Printing method	Direct Thermal Printing	Power Supply	DC 24V/2.5A
Dot pitch	567dots / line 512dots / line	Auto Cutter	Full or Partial
Character Size	ANK Character Font A : 12 x 24 dots Font B: 9x17 dots Chinese : 24 x 24 dots	Reliability	100KM
Barcode Type	UPC-A/UPC-E/JAN-13/EAN-13/EAN-8/ CODABAR/ITF/CODE39/CODE93/ CODE128	Work Environment	Temperature: 0-45%, Humidity: 10-80%
Interface	All-in-one Series, USB, Ethernet Interface	Storage Environment	Temperature: -10-60%, Humidity 10-90%
Paper Width	79.5 +/- 0.5mm	Driver	Win9x / Win Me / Win 2000 / Win 2003 / Win NT / Win XP / Win Vista / Win 7 / LINUX / OPOS
Paper Diameter	100mm	Compatible	ESC / POS
Paper Thickness	0.06-0.08mm	Print Speed	250mm/s
		Kitchen	Printing Support
		Paper near end sensor	Support
		Weight	1.90kg
		Dimension (W*D*H)	202x 143 x 144mm (LxWxH)
		Safety	3C, CE